

Package: files2prompt (via r-universe)

October 13, 2026

Type Package

Title RStudio addin to create prompt from code or text files in a project directory

Version 0.1.0

Author Sebastian Kranz

Maintainer Sebastian Kranz <sebastian.kranz@uni-ulm.de>

Description Can be customized using TOML based specifications.

License MIT

Encoding UTF-8

LazyData true

Depends restorepoint, stringi, RcppTOML, shiny, miniUI, tools, rstudioapi

Suggests clipr

RoxygenNote 7.2.3

Config/pak/sysreqs cmake make libicu-dev libuv1-dev zlib1g-dev

Repository <https://skranz.r-universe.dev>

Date/Publication 2026-05-06 08:55:34 UTC

RemoteUrl <https://github.com/skranz/files2prompt>

RemoteRef main

RemoteSha 9d341af6f63f30cacf9efde859f2d799479ed501

Contents

files2prompt	2
fp_parse_config	2
guess_token_num	3
hello	3
tpl_replace_whisker	4

Index	5
--------------	----------

files2prompt	<i>Build a prompt from text files</i>
--------------	---------------------------------------

Description

Reads a TOML specification in the collects the matching files and returns the assembled prompt that can be parsed to a LLM

Usage

```
files2prompt(
  config_file,
  root_dir = NULL,
  open = "{",
  close = "}",
  cfg = NULL,
  verbose = 1
)
```

Arguments

config_file	Path to the TOML config file.
root_dir	Override the 'root_dir' declared in the TOML. Use 'NULL' (default) to respect the spec.
open, close	Delimiters used in templates (default ' ... ').

Value

A character vector of length 1 containing the final prompt.

fp_parse_config	<i>Parse a TOML configuration file</i>
-----------------	--

Description

Parse a TOML configuration file

Usage

```
fp_parse_config(config_file)
```

Arguments

config_file	Path to the TOML config file.
-------------	-------------------------------

guess_token_num	<i>Heuristic token counter</i>
-----------------	--------------------------------

Description

Very rough estimate: `_1` token `'bytes_per_token'` bytes_. Useful when the Python `*tiktoken*` library is not available.

Usage

```
guess_token_num(txt, bytes_per_token = 4)
```

Arguments

<code>bytes_per_token</code>	Average bytes per token (default 4 — conservative).
<code>text</code>	Character string to measure.

Value

Integer token count.

hello	<i>Hello, World!</i>
-------	----------------------

Description

Prints 'Hello, world!'.

Usage

```
hello()
```

Examples

```
hello()
```

`tpl_replace_whisker` *Replaces whiskers in a template string*

Description

Replaces whiskers in a template string

Usage

```
tpl_replace_whisker(  
    txt,  
    values,  
    open = "{{",  
    close = "}}",  
    require_all_value = FALSE  
)
```

Arguments

<code>txt</code>	the tpl as a string
<code>values</code>	named list of values

Index

files2prompt, [2](#)
fp_parse_config, [2](#)
guess_token_num, [3](#)
hello, [3](#)
tpl_replace_whisker, [4](#)