

Package: shinyEventsUI (via r-universe)

October 14, 2026

Type Package

Title Some shiny widgets that only work with shinyEvents

Version 0.1.1

Date 2014-11-12

Author Sebastian Kranz

Maintainer Sebastian Kranz <sebastian.kranz@uni-ulm.de>

Description Some shiny widgets that only work with shinyEvents

License GPL >= 2.0

Depends shiny, shinyEvents, jsonlite, stringtools, dplyr

RoxygenNote 7.1.1

Config/pak/sysreqs cmake make libicu-dev libuv1-dev zlib1g-dev

Repository <https://skranz.r-universe.dev>

Date/Publication 2021-04-01 11:18:40 UTC

RemoteUrl <https://github.com/skranz/shinyEventsUI>

RemoteRef master

RemoteSha e05f1eb202f15174f054be914aed9920aa60148b

Contents

contextMenuHeader	2
fancytree	2
fancytreeHeader	3
handsontableHeader	3
hidden_div	3
html.image.animation.player	4
jqueryLayoutHeader	4
jqueryLayoutPage	4
jqueryLayoutPanels	5
nestedSelector	6
nestedSelectorHandler	6
radioBtnGroup	7

radioBtnGroupHandler	7
resizeLayout	8
timedMessage	8
uiContextMenuHeader	8
updateRadioBtnGroup	9
w2header	9
w2sidebar	9
w2tabs	10
w2tabs.add	10
w2tabs.close	10
w2toolbar	11

Index	12
--------------	-----------

contextMenuHeader	<i>Header for jqueryContextMenu</i>
-------------------	-------------------------------------

Description

Header for jqueryContextMenu

Usage

contextMenuHeader(...)

fancytree	<i>fancytree</i>
-----------	------------------

Description

fancytree

Usage

```
fancytree(  
  id,  
  source = NULL,  
  ...,  
  theme = "win8",  
  add.header = TRUE,  
  extensions = "",  
  auto_unbox = TRUE  
)
```

fancytreeHeader	<i>Header for fancytree</i>
-----------------	-----------------------------

Description

Header for fancytree

Usage

```
fancytreeHeader(  
    ...,  
    extensions = NULL,  
    theme = "win8",  
    add.filetree.js = TRUE,  
    add.context.menu = FALSE  
)
```

handsontableHeader	<i>Header for jqueryContextMenu</i>
--------------------	-------------------------------------

Description

Header for jqueryContextMenu

Usage

```
handsontableHeader(...)
```

hidden_div	<i>A div that is by default not shown</i>
------------	---

Description

A div that is by default not shown

Usage

```
hidden_div(id, ..., style = "")
```

html.image.animation.player

A simple image player for animations

Description

you can create svg images from multiple plots with record.svg.plots

Usage

```
html.image.animation.player(  
  container.id,  
  base.name = NULL,  
  image.files = NULL,  
  extension = "svg",  
  images.dir = file.path(getwd(), "images"),  
  loop.mode = c("none", "loop", "sweep")[1],  
  delay = 250,  
  add.container = TRUE  
)
```

jqueryLayoutHeader

A jqueryLayoutPage

Description

A jqueryLayoutPage

Usage

```
jqueryLayoutHeader(style = NULL)
```

jqueryLayoutPage

A jqueryLayoutPage

Description

A jqueryLayoutPage

Usage

```
jqueryLayoutPage(  
    ...,  
    id = "mainPane",  
    center = NULL,  
    north = NULL,  
    west = NULL,  
    east = NULL,  
    south = NULL,  
    panes = list(center = center, north = north, west = west, east = east, south = south),  
    json.opts = "",  
    style = NULL  
)
```

jqueryLayoutPanes

A jqueryLayoutPage

Description

A jqueryLayoutPage

Usage

```
jqueryLayoutPanes(  
    id = NULL,  
    center = NULL,  
    north = NULL,  
    west = NULL,  
    east = NULL,  
    south = NULL,  
    panes = list(north = north, west = west, center = center, east = east, south = south),  
    json.opts = "",  
    style = NULL,  
    js.do.layout = TRUE,  
    parent = "body",  
    parent.layout = NULL,  
    parent.pane = "center"  
)
```

nestedSelector	<i>Nested select menus that show associated div elements</i>
----------------	--

Description

Nested select menus that show associated div elements

Usage

```
nestedSelector(  
  id,  
  selectors,  
  label = "",  
  show.first = TRUE,  
  input.type = c("radioBtnGroup", "select")[1],  
  btn.size = "sm",  
  selector.par = list(),  
  scroll.top.sel = NULL  
)
```

nestedSelectorHandler	<i>Add a change handler to a nested selector</i>
-----------------------	--

Description

Add a change handler to a nested selector

Usage

```
nestedSelectorHandler(id, fun, ..., app = getApp())
```

Value

value a list with the values of all shown selector parts

radioBtnGroup	<i>A button group that acts like a radio button group</i>
---------------	---

Description

use radioBtnGroupHandler to add a handler for a value change

Usage

```
radioBtnGroup(  
    id,  
    labels,  
    values = seq_along(labels),  
    handler = NULL,  
    div.style = "",  
    div.extra.class = "",  
    btn.size = "xs",  
    btn.style = "",  
    panes = show.hide.containers,  
    show.hide.containers = NULL,  
    ...  
)
```

radioBtnGroupHandler	<i>Add change handler to a radio button group</i>
----------------------	---

Description

Add change handler to a radio button group

Usage

```
radioBtnGroupHandler(  
    id,  
    fun,  
    ...,  
    eventId = "radioBtnGroupChange",  
    app = getApp()  
)
```

Value

value the value of the selected button

resizeLayout	<i>Resize a jqueryLayout. May be useful if inner html has been dynamically changed and we have size="auto"</i>
--------------	--

Description

Resize a jqueryLayout. May be useful if inner html has been dynamically changed and we have size="auto"

Usage

```
resizeLayout(id, layout.var = paste0(id, "LayoutVar"))
```

timedMessage	<i>show a message in some outputUI for duration of millis milliseconds</i>
--------------	--

Description

show a message in some outputUI for duration of millis milliseconds

Usage

```
timedMessage(
  id,
  msg = "",
  html = msg,
  ui = HTML(html),
  millis = 3000,
  empty.msg = "",
  empty.ui = HTML(empty.msg),
  app = getApp()
)
```

uiContextMenuHeader	<i>Header for jqueryContextMenu</i>
---------------------	-------------------------------------

Description

Header for jqueryContextMenu

Usage

```
uiContextMenuHeader(...)
```

updateRadioBtnGroup	<i>Change selected button of a radion button group</i>
---------------------	--

Description

use radioBtnGroupHandler to add a handler for a value change

Usage

```
updateRadioBtnGroup(session = app$session, id, value, app = getApp())
```

w2header	<i>Header for w2ui widgets</i>
----------	--------------------------------

Description

Header for w2ui widgets

Usage

```
w2header(...)
```

w2sidebar	<i>Sidebar. See w2ui docs</i>
-----------	-------------------------------

Description

Sidebar. See w2ui docs

Usage

```
w2sidebar(
  id,
  img = NULL,
  nodes = NULL,
  ...,
  width = "100%",
  height = "100%",
  js.on.render = "",
  add.header = TRUE
)
```

w2tabs

Tabs. See w2ui docs

Description

Tabs. See w2ui docs

Usage

```
w2tabs(id, active = 1, tabs = NULL, js.on.render = NULL, add.header = TRUE)
```

Arguments

id	the id of the whole tabset
active	the index of the initially shown tab
tabs	a list of tabs each tab is itself a list. Example: tabs=list(list(id="newTab",caption="New Tab", div_id="tab4div", closable=TRUE, keep_closed_content=FALSE))) • id - the id of the tab • caption - the caption shown on the tab • div_id - the id of the div that contains the tab content • closable - if TRUE the tab can be closed by pressing on an "x" icon • keep_closed_content if FALSE (default) the tab div with div_id will be removed when the tab is closed. If TRUE the div will only be hidden.

w2tabs.add

Add a w2ui tab

Description

Add a w2ui tab

Usage

```
w2tabs.add(id, tabs = list(tab), tab, select = TRUE)
```

w2tabs.close

Close a w2ui tab

Description

Close a w2ui tab

Usage

```
w2tabs.close(id, tabId, destroy.content = FALSE)
```

`w2toolbar`*Toolbar or menubar. See w2ui docs*

Description

Toolbar or menubar. See w2ui docs

Usage

```
w2toolbar(id, items = NULL, js.on.render = NULL, add.header = TRUE)
```

Index

contextMenuHeader, [2](#)

fancytree, [2](#)
fancytreeHeader, [3](#)

handsontableHeader, [3](#)
hidden_div, [3](#)
html.image.animation.player, [4](#)

jqueryLayoutHeader, [4](#)
jqueryLayoutPage, [4](#)
jqueryLayoutPanes, [5](#)

nestedSelector, [6](#)
nestedSelectorHandler, [6](#)

radioBtnGroup, [7](#)
radioBtnGroupHandler, [7](#)
resizeLayout, [8](#)

timedMessage, [8](#)

uiContextMenuHeader, [8](#)
updateRadioBtnGroup, [9](#)

w2header, [9](#)
w2sidebar, [9](#)
w2tabs, [10](#)
w2tabs.add, [10](#)
w2tabs.close, [10](#)
w2toolbar, [11](#)