

Package: xglue (via r-universe)

August 19, 2024

Type Package

Title Extended glue. Write collapse and by Uses a template file with a special syntax.

Version 0.1.0

Author Sebastian Kranz

Maintainer Sebastian Kranz <sebastian.kranz@uni-ulm.de>

Description Extended glue. Add in the string to be glued blocks that specify collapse operations on vectors, and allow to operate on a grouped data frame

License GPL (>=2.0)

Encoding UTF-8

LazyData true

Depends glue, dplyr, stringtools, restorepoint

RoxygenNote 7.1.1

Repository <https://skranz.r-universe.dev>

RemoteUrl <https://github.com/skranz/xglue>

RemoteRef main

RemoteSha a537ada815486cc71e57f99928433b44b1fd5e8d

Contents

find.nested.blocks	2
xglue	2

Index	4
--------------	----------

`find.nested.blocks` *Find nested blocks in a text*

Description

Blocks must start and end with separate header and trailer lines, respectively e.g.

Usage

```
find.nested.blocks(txt, open = "#<", close = "#>")
```

Arguments

<code>txt</code>	a character vector
<code>open</code>	start of a block's header line, by default "#<"
<code>close</code>	start of a block's trailer line by default "#>".

Details

```
#< collapse ", "  
#>
```

`xglue` *Perform xglue operation on a template text*

Description

Perform xglue operation on a template text

Usage

```
xglue(  
  txt,  
  envir = parent.frame(),  
  open = "{",  
  close = "}",  
  pre.open = "<<",  
  pre.close = ">>",  
  block.open = "#<",  
  block.close = "#>",  
  enclos = parent.frame(),  
  newline = "<<newline>>",  
  just.pre = FALSE  
)
```

Arguments

<code>txt</code>	The template text on which <code>xglue</code> operations shall be performed
<code>envir</code>	Environment or list that contains objects whose value is spliced in. By default the environment from which <code>xglue</code> is called.
<code>open</code>	the opening string of glue whiskers
<code>close</code>	the closing string of glue whiskers
<code>pre.open</code>	the opening string of glue whiskers when pre compiling pre blocks
<code>pre.close</code>	the closing string of glue whiskers when pre compiling pre blocks
<code>block.open</code>	start of a block's header line, by default "#<"
<code>block.close</code>	start of a block's trailer line by default "#>".
<code>enclos</code>	If <code>envir</code> is a list the enclosing environment.
<code>just.pre</code>	Just compile the pre blocks and return the resulting template.

Value

The glued text as a single character

Index

`find.nested.blocks`, [2](#)

`xglue`, [2](#)